

# **Idemitsu SM/CF 15W-40**

## **Description**

**Idemitsu SM/CF 15W-40** is a premium engine oil formulated from specially refined paraffinic base oils, combined with the most modern friction modifier, detergent-dispersant, anti-corrosion, anti-wear and other protective properties and it meets API grade: SM/CF requirement.

## **Application**

Recommended for all modern 4-stroke gasoline engine and turbo/ supercharged engine.

## **Characteristics**

1. Outstanding oxidation and thermal stability.
2. Wide temperature range of 15W-40.
  - High fluidity at low temperature and excellent cold start
  - Great durability at high temperature
3. Excellent control of deposits, rust, wear and bearing corrosion.
4. Excellent fuel economy.
5. Meets the requirement of :-  
API: SM/CF
6. Prolongs engine life and improve running efficiency.

## **Packing**

6 x 4 Litres Carton, 20 Litres Pail, 200 Litres Drum

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

## Lubricant Product Information

### Typical Specifications

### Idemitsu SM/CF 15W-40

	<b>ASTM METHOD</b>	
SAE Viscosity grade		15W-40
Color (Appearance)		Brown
Density 15 °C g/cm <sup>3</sup>	D-4052	0.8755
Flash Point (COC) °C	D-92	238
Viscosity, cSt @ 40 °C	D-445	106.2
@ 100 °C		13.89
Pour Point °C	D-97	-42.5
Viscosity Index	D-2270	131
TBN, HClO <sub>4</sub> (mgKOH/g)	D-2896	7.02
Foaming @ 93.5°C (ml)	D-892	10-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.