Lubricants info.



Idemitsu Kosan Co.,Ltd.

Lubricant Product Information



Daphne Super Coat WR

High Performance Anti Rust Oil

Description

Daphne Super Coat WR is a barium-free rust preventive oil with excellent water displacement properties. It has been formulated with highly refined mineral base oil with rust-preventive additives and water displacement agents to provide excellent rust prevention performance through the fast removal of water and moisture from the metal surfaces.

Application

Recommended as a water displacement type rust preventive oil with wide range of uses. It is especially recommended as rust prevention and cleaning/rinsing for:

- Machine and metal parts after cutting, grinding, press working and drawing processes.
- Bearings, tooling, gears and gauges.
- All types of steel plates (in-process rust prevention)
- Processed parts that require removal of water and moisture.

Characteristics

- 1. Excellent water displacement and rust prevention abilities.
- Fast water displacement action 90 seconds to effectively displace water from metal surfaces.
- 3. Blue transparent appearance for easy identification and removal.
- 4. Economy less carry away due to low viscosity.

Packing

20L pail, 200L drum

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

<u>Lubricants info.</u>



Idemitsu Kosan Co.,Ltd.

Lubricant Product Information



Typical Specifications

Daphne Super Coat WR

	ASTM	
	METHOD	
Appearance	-	Blue transparent
Specific Density 15 ℃ g/cm ³	D-4052	0.8071
Flash Point (COC) ℃	D-92	92
Viscosity, cSt @ 40 ℃	D-445	2.507
Pour Point, ℃	D-6749	<-40.0
Total Acid Value (mgKOH/g)	D-974	3.59
Total Base Number (mgKOH/g)	D-2896	2.50
Salt Spray Test 24 Hours	-	A Class

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.