

Idemitsu 4T SJ/MA 10W-30

Description

Idemitsu 4T SJ/MA 10W-30 is a motorcycle engine oil specially formulated to provide excellent engine wear & tear protection. In addition, this technologically advanced formulation offers significant fuel savings.

Application

Recommended for all modern 4T engines.

Characteristics

1. Mineral based engine oil.
2. Wide temperature range of 10W-30.
 - High fluidity at low temperature and excellent cold start
 - Great durability at high temperature
3. Excellent high temperature protection.
4. Superb fuel economy.
5. Meets the requirement of :-
API SJ & JASO MA

Packing

24 x 1 Litre Carton, 200 Litres Drum

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

Typical Specifications**Idemitsu 4T SJ/MA 10W-30**

	ASTM METHOD	
SAE Viscosity grade		10W-30
Color (Appearance)	D-1500	L 3.5 (Dark Brown)
Density 15 °C g/cm ³	D-4052	0.8652
Flash Point (COC) °C	D-92	232
Viscosity, cSt @ 40 °C	D-445	67.37
@ 100 °C	D-445	10.24
Pour Point °C	D-97	-35
Viscosity Index	D-2270	138
TBN,HClO ₄ (mgKOH/g)	D-2896	7.63
Foaming @ 93.5°C (ml)	D-892	0-0
Noack Test 250 °C, 1Hr @ wt%	D-5800	9.0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.